

FPL1000 Product Safety Data Card

MSDS

Product Marking

Product Name	Cable Pulling Lubricant	Type	Mixture
Main Usage	The laying of cables through pipes	Code	FPL1000
Major Component	Petroleum wax、Petroleum jelly、cellulose gum、Antimicrobial agent、Deionized water		

Physicochemical Property

Appearance	Pale yellow paste	PH Value	7
Solubleness	Soluble in water	Relative Density	0.98

Combustion And Explosion Hazard

No burning, No explosion risk

Hazard Of Contact Behavior

Exposure Limit	The biggest step in	Invasion Way	Skin exposure
Health Hazard	No burns, corrosion, poisoning and other damage to skin contact		

Packing Storage

Risk Category	Common chemical	Label Of Package Of Dangerous Goods	regular packing
Precautions For Storage And Transportation	Storage and transportation of common chemicals without leakage		

First-aid

Skin Exposure	Rinse immediately with plenty of running water	Inhalation	nothing
Eye Contact	Flush immediately with plenty of water and see a doctor if it's serious	Wrongly	Seek medical treatment in time

Protective Measures

Respiratory Protection	Overflow time, Wear protective masks	Eye Protection	Wear protective glasses
Protective Suit	Wear the uniform	Hand Protection	Wear protective gloves
Engineering Control	nothing		

Leakage Processing

Absorb with an absorbent substance such as sand or soil, or rinse with water
--

Environmental Message

Storage Precautions	Avoid direct sunlight and close to heat source. Store in a cool place at room temperature
Abolishing The Disposal Method	Centralized management and processing after use

Notes: This quality tracking card is used as reference data, comprehensive instructions, no natural hazards, if you have any questions, please consult the technical department of the company.



www.fcst.com

www.micro-duct.com